

according to UK REACH Regulation

DEKASEAL 8869 D

Revision date: 11.09.2019 Product code: 1042 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DEKASEAL 8869 D

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Barrier (Sealant)

Uses advised against

No further relevant information available.

1.3. Details of the supplier of the safety data sheet

Company name: DINOL GmbH

 Street:
 Pyrmonter Strasse 76

 Place:
 D-32676 Luegde

 Telephone:
 + 49 (0) 5281 982980

+ 49 (0) 5281 982980 Telefax: + 49 (0) 5281 9829860

e-mail: msds@dinol.com

Contact person: Labor

Responsible Department: msds@dinol.com

1.4. Emergency telephone Giftnotruf Berlin: +49 30 30686 700 (Beratung in Deutsch und Englisch)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories:

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Kohlenwasserstoffe, C7-C9, n-Alkane, Isoalkane, Cyclics

Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclics, <2% Aromaten Kohlenwasserstoffe, C6-C7, n-Alkane,Isoalkane, cyclische, <5% n-Hexan

Signal word: Warning

Pictograms:



Hazard statements

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.



according to UK REACH Regulation

DEKASEAL 8869 D

Revision date: 11.09.2019 Product code: 1042 Page 2 of 12

P405

Store locked up.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

| CAS No | Chemical name | | | | |
|------------|--|-----------------------------------|------------------|-------------|--|
| | EC No | Index No | REACH No | | |
| | GHS Classification | • | • | | |
| | Kohlenwasserstoffe, C7-C9, n-Alka | ine, Isoalkane, Cyclics | | 10 - < 15 % | |
| | 920-750-0 | | 01-2119473851-33 | | |
| | Flam. Liq. 2, STOT SE 3, Asp. Tox | . 1, Aquatic Chronic 2; H225 H336 | H304 H411 | | |
| 64742-49-0 | Kohlenwasserstoffe, C9-C10, n-Alk | ane, Isoalkane, Cyclics, <2% Aror | naten | 5 - < 10 % | |
| | 927-241-2 | | 01-2119471843-32 | | |
| | Flam. Liq. 3, STOT SE 3, Asp. Tox | . 1, Aquatic Chronic 3; H226 H336 | H304 H412 EUH066 | | |
| | Kohlenwasserstoffe, C6-C7, n-Alka | 1 - < 5 % | | | |
| | 921-024-6 | | 01-2119475514-35 | | |
| | Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411 | | | | |
| 128-37-0 | 2,6-Di-tert-butyl-p-kresol | < 1 % | | | |
| | 204-881-4 | | | | |
| | Aquatic Acute 1, Aquatic Chronic 1 | | | | |
| 110-82-7 | Cyclohexan | < 1 % | | | |
| | 203-806-2 | 601-017-00-1 | | | |
| | Flam. Liq. 2, Skin Irrit. 2, STOT SE H315 H336 H304 H400 H410 | | | | |
| 131-57-7 | 2-Hydroxy-4-Methoxy-Benzophon | < 1 % | | | |
| | 205-031-5 | | 01-2119976330-39 | | |
| | Aquatic Acute 1, Aquatic Chronic 2; H400 H411 | | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|------------|--------------------------|---|-------------|
| | Specific Conc. | Limits, M-factors and ATE | |
| | 920-750-0 | Kohlenwasserstoffe, C7-C9, n-Alkane, Isoalkane, Cyclics | 10 - < 15 % |
| | inhalation: LC | 50 = 23,3 mg/l (vapours); dermal: LD50 = 2800-3100 mg/kg | |
| 64742-49-0 | 927-241-2 | Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclics, <2% Aromaten | 5 - < 10 % |
| | inhalation: LC: mg/kg | 50 = >5000 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 | |
| | 921-024-6 | Kohlenwasserstoffe, C6-C7, n-Alkane, Isoalkane, cyclische, <5% n-Hexan | 1 - < 5 % |
| | inhalation: LC: mg/kg | 50 = > 20 mg/l (vapours); dermal: LD50 = >2920 mg/kg; oral: LD50 = > 5000 | |
| 128-37-0 | 204-881-4 | 2,6-Di-tert-butyl-p-kresol | < 1 % |
| | dermal: LD50 | = >5000 mg/kg; oral: LD50 = >5000 mg/kg | |

Further Information

Hydrocarbons meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).



according to UK REACH Regulation

DEKASEAL 8869 D

Revision date: 11.09.2019 Product code: 1042 Page 3 of 12

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Do NOT induce vomiting.

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder. Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For emergency responders

For further specification, refer to section 8 of the SDS.

6.2. Environmental precautions

Cover drains. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.



according to UK REACH Regulation

DEKASEAL 8869 D

Revision date: 11.09.2019 Product code: 1042 Page 4 of 12

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

Other information

No information available.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe gas/vapour/aerosol.

Advice on general occupational hygiene

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

No further relevant information available.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place. Keep container dry.

Hints on joint storage

Not required.

Further information on storage conditions

Keep container tightly closed and in a well-ventilated place. Keep container dry.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m³ | fibres/ml | Category | Origin |
|------------|---------------------------------|-----|-------|-----------|---------------|--------|
| 128-37-0 | 2,6-Di-tert-butyl-p-cresol | - | 10 | | TWA (8 h) | WEL |
| 7727-43-7 | Barium sulphate, inhalable dust | - | 10 | | TWA (8 h) | WEL |
| 110-82-7 | Cyclohexane | 100 | 350 | | TWA (8 h) | WEL |
| | | 300 | 1050 | | STEL (15 min) | WEL |
| 14807-96-6 | Talc respirable dust | - | 1 | | TWA (8 h) | WEL |



according to UK REACH Regulation

DEKASEAL 8869 D

Revision date: 11.09.2019 Product code: 1042 Page 5 of 12

DNEL/DMEL values

| CAS No | Substance | | | |
|--------------------------|---|-----------------------|----------|-----------------------|
| DNEL type | • | Exposure route | Effect | Value |
| 7727-43-7 | Bariumsulfat | | | |
| Worker DNEL, | long-term | inhalation | systemic | 10 mg/m³ |
| Worker DNEL, | long-term | inhalation | local | 10 mg/m³ |
| Consumer DN | EL, long-term | inhalation | systemic | 10 mg/m³ |
| Consumer DN | EL, long-term | oral | systemic | 13000 mg/kg bw/day |
| | Kohlenwasserstoffe, C7-C9, n-Alkane, Isoalkane, Cy | yclics | | |
| Worker DNEL, | long-term | dermal | systemic | 773 mg/kg bw/day |
| Consumer DN | EL, long-term | dermal | systemic | 699 mg/kg bw/day |
| Consumer DN | EL, long-term | oral | systemic | 699 mg/kg bw/day |
| Worker DNEL, | long-term | inhalation | systemic | 2035 mg/m³ |
| Consumer DN | EL, long-term | inhalation | systemic | 608 mg/m³ |
| 64742-49-0 | Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, C | Cyclics, <2% Aromaten | | |
| Worker DNEL, | long-term | inhalation | systemic | 871 mg/m³ |
| Worker DNEL, | long-term | dermal | systemic | 77 mg/kg bw/day |
| Consumer DN | EL, long-term | inhalation | systemic | 185 mg/m³ |
| Consumer DN | EL, long-term | dermal | systemic | 46 mg/kg bw/day |
| Consumer DN | EL, long-term | oral | systemic | 46 mg/kg bw/day |
| | Kohlenwasserstoffe, C6-C7, n-Alkane, Isoalkane, cyc | clische, <5% n-Hexan | | |
| Worker DNEL, | long-term | dermal | systemic | 773 mg/kg bw/day |
| Consumer DN | EL, long-term | dermal | systemic | 699 mg/kg bw/day |
| Consumer DN | EL, long-term | oral | systemic | 699 mg/kg bw/day |
| Worker DNEL, | long-term | inhalation | systemic | 2035 mg/m³ |
| Consumer DN | EL, long-term | inhalation | systemic | 608 mg/m³ |
| 128-37-0 | 2,6-Di-tert-butyl-p-kresol | | | |
| Worker DNEL, | long-term | inhalation | systemic | 3,5 mg/m³ |
| Worker DNEL, | acute | inhalation | systemic | 18 mg/m³ |
| Worker DNEL, | long-term | dermal | systemic | 0,5 mg/kg bw/day |
| Worker DNEL, acute | | dermal | systemic | 19 mg/kg bw/day |
| Consumer DNEL, long-term | | inhalation | systemic | 0,78 mg/m³ |
| Consumer DNEL, acute | | inhalation | systemic | 3,1 mg/m³ |
| Consumer DNEL, long-term | | dermal | systemic | 0,25 mg/kg bw/day |
| Consumer DNEL, acute | | dermal | systemic | 6,7 mg/kg bw/day |
| Consumer DN | EL, long-term | oral | systemic | 0,25 mg/kg bw/day |
| Consumer DN | EL, acute | oral | systemic | 1 mg/kg bw/day |



according to UK REACH Regulation

DEKASEAL 8869 D

Revision date: 11.09.2019 Product code: 1042 Page 6 of 12

PNEC values

| CAS No | Substance | |
|---|--------------------------------------|----------------------------|
| Environment | al compartment | Value |
| 7727-43-7 | Bariumsulfat | |
| Freshwater | | 0,115 mg/l |
| Freshwater | sediment | 600,4 mg/kg |
| Micro-organi | sms in sewage treatment plants (STP) | 62,2 mg/l |
| Soil | | 207,7 mg/kg |
| 128-37-0 | 2,6-Di-tert-butyl-p-kresol | |
| Freshwater | | 0,000199-0,0023 mg/l |
| Marine water | | 0,0000199-0,0002 3 mg/l |
| Freshwater sediment | | 0,0996-3,4 mg/kg |
| Marine sedir | nent | 0,00996-0,34 mg/kg |
| Micro-organisms in sewage treatment plants (STP) 0,17-100 m | | 0,17-100 mg/kg |

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Recommended eye protection articles :

Eye glasses with side protection (DIN EN 166)

Hand protection

Recommended glove articles

FKM (fluoro rubber), Breakthrough time (maximum wearing time): 480 min.

NBR (Nitrile rubber), Breakthrough time (maximum wearing time): 480 min.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves have to be replaced at the first sign of deterioration.

Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. gas filtering equipment (EN 141). Filter material/medium : A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Paste



according to UK REACH Regulation

DEKASEAL 8869 D

Revision date: 11.09.2019 Product code: 1042 Page 7 of 12

Colour: grey

Odour: characteristic
Odour threshold: not determined

Test method

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

89 - 107 °C

boiling range:

Flash point: 70 °C

Flammability

Solid/liquid: not determined
Gas: not determined

Explosive properties

not determined

Lower explosion limits:0,9 vol. %Upper explosion limits:7 vol. %Auto-ignition temperature:> 200 °C

Self-ignition temperature

Solid: not self-igniting
Gas: not self-igniting

Oxidizing properties

not determined

pH-Value (at 20 °C):

Viscosity / dynamic: 5000 mPa·s

(at 20 °C)

Viscosity / kinematic: not determined
Water solubility: Immiscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined
Vapour pressure: 20 hPa

(at 20 °C)

Density: 1,55 g/cm³ DIN 51757

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion:

No data available

Other safety characteristics

Solvent content: 25,5 % Solid content: 74,0 %

Further InformationNo information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability



according to UK REACH Regulation

DEKASEAL 8869 D

Revision date: 11.09.2019 Product code: 1042 Page 8 of 12

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | | |
|------------|--|----------------------|-------------|-------------------------|--------|--------|
| | Exposure route | Dose | | Species | Source | Method |
| | Kohlenwasserstoffe, C7- | C9, n-Alkane, l | lsoalkane, | Cyclics | | |
| | dermal | LD50 2 3100 mg/kg | 2800- | Rat | | |
| | inhalation (4 h) vapour | LC50 | 23,3 mg/l | Rat | | |
| 64742-49-0 | Kohlenwasserstoffe, C9- | C10, n-Alkane, | , Isoalkane | , Cyclics, <2% Aromaten | | |
| | oral | LD50 = mg/kg | >5000 | Rat | | |
| | dermal | LD50 = mg/kg | >5000 | Rabbit | | |
| | inhalation vapour | LC50 : | >5000 | Rat | | |
| | Kohlenwasserstoffe, C6-C7, n-Alkane, Isoalkane, cyclische, <5% n-Hexan | | | | | |
| | oral | LD50 : | > 5000 | Rat | | |
| | dermal | LD50 : mg/kg | >2920 | Rabbit | | |
| | inhalation (4 h) vapour | | > 20 mg/l | Rat | | |
| 128-37-0 | 2,6-Di-tert-butyl-p-kresol | | | | | |
| | oral | LD50 : mg/kg | >5000 | Rat | | |
| | dermal | LD50 : mg/kg | >5000 | Rat | | |

Irritation and corrosivity

Based on available data, the classification criteria are not met. Irritating to eyes and skin.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.



according to UK REACH Regulation

DEKASEAL 8869 D

Revision date: 11.09.2019 Product code: 1042 Page 9 of 12

STOT-repeated exposure

Based on available data, the classification criteria are not met. Danger of serious damage to health by prolonged exposure.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

| CAS No | Chemical name | | | | | |
|----------|----------------------------|-------------------------|-------------------|--------|--------|--|
| | Aquatic toxicity | Dose | [h] [d] Species | Source | Method | |
| 128-37-0 | 2,6-Di-tert-butyl-p-kresol | | | | | |
| | 1 | EC50 0,48- 0,61 mg/l | 48 h | | | |

12.2. Persistence and degradability

There are no data available on the mixture itself.

| CAS No | Chemical name | | | | | |
|------------|--|--------|----|--------|--|--|
| | Method | Value | d | Source | | |
| | Evaluation | | | | | |
| 64742-49-0 | Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cyclics, <2% Aromaten | | | | | |
| | OECD 301F | > 60 % | 28 | | | |
| | Leicht biologisch abbaubar (nach OECD-Kriterien). | | | | | |

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|----------|----------------------------|---------|
| 128-37-0 | 2,6-Di-tert-butyl-p-kresol | 5,10 |

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

not applicable

12.7. Other adverse effects

No information available.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Do not mix with other wastes.

List of Wastes Code - residues/unused products



according to UK REACH Regulation

DEKASEAL 8869 D

Revision date: 11.09.2019 Product code: 1042 Page 10 of 12

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

Contaminated packaging

Dispose according to legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.Marine pollutant:no

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Tansport classification ADR/IMGD is based on packaging >30ltr(IMDG), <450ltr(ADR). For other packaging until different classification can apply.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 57

GB - EN Print date: 14.07.2021



according to UK REACH Regulation

DEKASEAL 8869 D

Product code: 1042 Revision date: 11.09.2019 Page 11 of 12

2004/42/EC (VOC): 25.51 %

395,5 q/l

Information according to 2012/18/EU

(SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

Additional information: 0

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

> work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

This mixture contains the following substances of very high concern (SVHC) which are included in the

Candidate List according to Article 59 of REACH: none

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

| Classification | Classification procedure |
|-------------------------|--------------------------|
| STOT SE 3; H336 | Calculation method |
| Aquatic Chronic 3; H412 | Calculation method |

Re

| OT SE 3; H336 | Calculation method | | | |
|---|------------------------------|--|--|--|
| atic Chronic 3; H412 | Calculation method | | | |
| elevant H and EUH statements (number and full text) | | | | |
| H225 Highly | flammable liquid and vapour. | | | |

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

H226

H304

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product



according to UK REACH Regulation

DEKASEAL 8869 D

Revision date: 11.09.2019 Product code: 1042 Page 12 of 12

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)